# *Optimizing Epileptic Seizure Detection Using EEG Signals with Deep Learning Techniques*

Synopsis of the Research Proposal

Submitted for the Registration in the

**Ph.D. Program (Part-Time) in Engineering**

By

*RAJAN KUMAR JHA (E.No: 23RDCDIUJND02013)*

**Under Supervision of**

*DR. A. K. SAINI*

*DIRECTOR ICFAITECH*

**THE ICFAI UNIVERSITY JAIPUR**

# PROPOSED SUMMARY / ABSTRACT

Epilepsy, a neurological disorder characterized by recurrent seizures, poses a significant public health challenge. Accurate and timely seizure detection is crucial for effective patient management and improved quality of life. Electroencephalography (EEG) signals provide valuable insights into brain activity, making them a cornerstone for seizure diagnosis. However, manual analysis of EEG data is time-consuming, subjective, and prone to human error. This project proposes to develop a novel approach for improved classification of epileptic and non-epileptic seizures in EEG signals using hybrid deep learning models.

Traditional machine learning methods for EEG seizure classification often face limitations in capturing the complex non-linear dynamics inherent in brain signals. Deep learning architectures, such as Convolutional Neural Networks (CNNs) and Recurrent Neural Networks (RNNs), have shown promise [1] in extracting intricate features from EEG data. However, individual deep learning models may have limitations in capturing both spatial and temporal dependencies effectively.

This project aims to address these challenges by developing a hybrid deep learning framework that leverages the strengths of different architectures. Specifically, we propose to integrate CNNs and RNNs into a synergistic model. CNNs will be employed to extract spatial features from EEG signals, capturing local patterns and spatial correlations. RNNs, such as Long Short-Term Memory (LSTM) networks, will be utilized to capture temporal dependencies and long-range temporal patterns in the EEG data.

The proposed hybrid model will be trained and evaluated on a comprehensive dataset of EEG recordings from epileptic and non-epileptic patients. Performance metrics such as accuracy, sensitivity, specificity, and F1-score will be used to assess the model's effectiveness. We will compare the performance of the proposed hybrid model with individual CNN and RNN models, as well as with traditional machine learning methods, to demonstrate its superior classification accuracy.

# 1. INTRODUCTION

## 1.1 Introduction

Seizures, sudden, unpredictable increases in brain activity, can cause a wide range of mental and physical symptoms. They can be divided into two broad categories: epileptic seizures and non-epileptic seizures [1]. Their causes, procedures, and therapeutic approaches vary, despite the fact that they both involve incidents that may appear similar to the untrained eye.

Epilepsy, a neurological disorder that affects the brain's electrical system, is commonly linked to epileptic seizures, which are caused by abnormal electrical activity in the brain. During an epileptic seizure, neurons, or brain cells, fire irregularly, momentarily impairing brain function. These seizures are frequently separated into two main types: focal (partial) seizures, which originate in a particular area of the brain, and generalized seizures, which impact the whole brain [2]. The most common kind of generalized seizure in which the patient loses consciousness and has intense muscular spasms is the tonic-clonic seizure, which was once referred to as a grand mal seizure.

Epileptic seizures can be caused by a variety of factors, such as infections, brain trauma, heredity, and underlying neurological problems. A common diagnostic tool is an electroencephalogram (EEG), which records the electrical activity in the brain. Anti-seizure medicine is the cornerstone of treatment for epileptic seizures; nevertheless, certain individuals may additionally require surgery or other therapies if anti-seizure medication is insufficient [3].

On the other hand, non-epileptic seizures (NES) are events that mimic epileptic seizures but do not include abnormal brain activity. Psychological difficulties include stress, trauma, or underlying mental health illnesses like melancholy or anxiety are typically the cause of severe seizures. The most common kind of NES, known as psychogenic non-epileptic seizures (PNES), is believed to be a physical manifestation of mental distress or psychological trauma [4].

Despite having a similar appearance to epileptic seizures, NES episodes do not exhibit the same aberrant brain activity on an EEG. To make the diagnosis, epilepsy is often ruled out using EEG monitoring and other procedures. Treatment for NES focuses on treating the psychological causes, including counseling, stress management, and therapy, rather than

using anti-seizure medications [5].

Seizures, whether or not a person is epileptic, can have a major influence on their quality of life. Therefore, accurate diagnosis and therapy are crucial. With the right care, people may manage both conditions even if the approaches are completely different. Neurological treatment is necessary for epileptic seizures, but NES requires a focus on psychological support.

Electroencephalography (EEG) is a non-invasive medical imaging technique used to study neurological disorders. The neural function of the human brain not only reflects brain activity but also the state of human activity as a whole. The EEG signal shows the various brain functions through a spectrum of frequencies and energy levels recorded by electrodes placed on the scalp. These brain rhythms are defined by a variety of frequency ranges, such as delta (δ) waves between 0.5 and 4 Hz, gamma (γ) waves above 30 Hz, beta (β) waves between 14 and 30 Hz, and α (α) waves between 8 and 13 Hz. and Theta(θ) is located at 4-7.5 Hz. The three most common forms of artifacts in EEG signal processing are EOG (Blinking Eyes and Eye Artefacts), EMG (Muscle Activation), and ECG (Heart Activation). The electrooculogram (EOG), on the other hand, is the most obvious artifact and is caused by a potential difference between the retina and the cornea that is much larger than the potential in the brain [7]. The EEG recordings of individuals with epilepsy showed two types of aberrant activity: seizures recorded during seizures, which are abnormal signals, and ictal activity, which is activity recorded during seizures. Unintentional transient waveforms are EEG characteristics that are active across time, such as single spikes, spike sequences, spikes, or spike complexes. EEG characteristics of seizures include continuous discharge with polymorphic waveforms of changing amplitude and frequency, spikes and spikes, rhythmic hypersynchronization or computer idleness, and durations greater than the typical length of these anomalies throughout seizure period. In most cases, epilepsy may be identified by a skilled neurophysiologist visually scanning the EEG record during electroencephalography and episodes. However, visually evaluating large amounts of EEG data has serious drawbacks. Visual examination is time-consuming and useless, especially when it comes to long-term recordkeeping. Additionally, neurophysiologists may disagree with the same record due to the subjective nature of the analysis and the diversity in spike patterns between episodes [8]. Additionally, the EEG pattern that identifies seizures is similar to waves that are a component of background noise and artifacts (especially in other

cranial recordings), such as muscular activity, ECG, electrode "popular," electrical interference, blinking, and other ocular movements. These factors make methods for automatically detecting seizures and seizure spikes potentially valuable clinical instruments for more impartial and computationally effective EEG data processing [9].

## 1.2 Neural Activities

Neurones and other nervous system cells transmit information from the brain to non-neuronal cells. They self-organize into a complex network that performs functions of the nervous system. The size, structure, and activity of nerve cells can vary greatly, even though they are all referred to as neurons [10]. Neurons can be grouped according to their shape or function. Three groups of neurons—motor neurones, inter-neurons, sensory neurones, and neurones related to sensory receptors—can be categorized using the latter approach.




Figure 1.1: Synaptic activities in the neurons [56]

They are mostly composed of elinated axons, which are connected to different areas of the central nervous system. The human cerebral cortex has a thickness of 2-4 mm. The cortical surface is heavily bent by ridges and valleys of different widths, and over 1010 neurons are dispersed over an area of up to 2.5 square meters. The left and right symmetrical hemispheres that comprise the cortex are separated by deep longitudinal fissures, sometimes known as central grooves. The occipital lobe, which deals with vision; the temporal lobe, which deals with memory, feeling speech, emotion, hearing, and language; the frontal lobe, which deals with decision-making, motion speaking, problem-solving, and planning; and the Ye, which deals with receiving, reading, and understanding the body's sensory information, are the lobes that make up each cerebral hemisphere and are named after the skull that covers each brain.

## 1.3 Brain Rhythms

The electrical activity of the cerebral cortex is sometimes called the rhythm because the recorded signal exhibits periodic oscillations. A wide range of brain electrical cycles are influenced by the subject's mental state, including sleep, arousal, and attention. Often, the rhythm is defined by its relative loudness and frequency range. In contrast, the frequency ranges of the five brain waves allow them to be identified. These frequency ranges are α(α), θ(θ), β(β), Δ(δ), and γ(γ), in that sequence, from low frequency to high frequency. In 1929, Berger made the initial proposal for alpha and beta waves. In 1938, Jasper and Andrews defined "gamma" waves as those that exceeded 30 Hz. A few years prior, in 1936, Walter had introduced the delta rhythm to denote all frequencies below the alpha range and theta waves to the frequencies in the 4-7.5 Hz range.




Figure 1.2: Typical normal brain waves in the EEG [56]

Even with trained eyes, it can be difficult to understand and recognize brain rhythms and changes in the scalp EEG. The essential waves from the EEG should be able to be examined and separated by new applications utilizing advanced signal processing technology. For instance, background and foreground EEG are quite subjective and only depend on anomalies and applications. Brain potentials elicited by various sensory and cognitive stimuli (also called "evoked potentials, or EPs") and spontaneous brain activity (sometimes called "background EEG") are the two primary forms of EEG signals [12].

## 1.4 Electroencephalogram

Out of all the systems in the human body, the brain is the most noticeable and sophisticated organ. It shows a wide range of time and space dynamics. Electroencephalography (EEG) is a medical process used to read the electrical activity of the brain's scalp. The human brain is

also known as the brain in medical parlance. The electroencephalogram (EEG) signal rapidly records the self-generating activity of the brain [1]. EEG is the term used to describe brain activity that signals and is attracted to the head. It is created by bombarding the brain's neurons. Applying many electrodes to the scalp allows for the measurement of a short time span of 20 to 40 minutes.




Figure 1.3: Bipolar Recording position [57]

### 1.4.1 EEG Generation

Despite the relatively modest amplitude level of the input, the scalp electrode system may provide a recording potential proportional to the number of neurons in the excited state. The amplifier is used to increase the signal level for further processing [5]. The three components of the brain's structure are the brain, cerebellum, and brainstem. Movement, conscious emotions, and mental state are characterized by this area of the brain. The cerebellum area affects voluntary behaviors such as muscular exercise. It is clear that both cerebral and systemic disorders can be evaluated using the electrical impulses produced by the brain. The area of the brainstem that controls biorhythm, neurohormones, cardiac regulation, and respiratory function because the current that flows between the brain cells in the cerebral cortex is produced by the EEG signal. When neurons are triggered, current flows from the dendrites to the synaptic excitability of the neurons. This current produces a secondary current field in addition to a magnetic field. The magnetic field can be measured by an electromyography machine (EMG) or by an electric motor field that is sensed in the scalp's EEG system.

### 1.4.2 EEG Recording

Bipolar and referential recordings are frequently used to visually record and evaluate EEG. A change is recorded using a simple electrical current meter. However, they have recently been captured with a multi-electrode EEG device. After the attenuated signal channel has been amplified by each amplifier, the filter noise elimination system records and [4], [9]. EEG is later incorporated to the system. High sample rates and more quantitative signal processing techniques make it easy to correctly analyze EEG signals since the computer system can store a large amount of data.

# 2. LITERATURE REVIEW

Reviews of the literature in the fields of feature extraction, EEG signal processing, and machine learning techniques used for EEG signal classification are included here. Our research focuses on classifying EEG data that are attributed to seizures. Usually, the goal of this research is to distinguish between seizures and non-seizures. From a medical standpoint, this is important since the two types of seizures are very different even if they exhibit the same behavior. The two are also handled quite differently. Seizures are normally caused by our brains, whereas non-seizures are not. Any other disease that affects our body, such high blood pressure, excessive blood sugar, etc., causes them. Therefore, it is an important issue that computer scientists need to tackle. because this classification of automation strategies is necessary. In order to detect epilepsy, many researchers have begun investigating some more effective techniques for analyzing and classifying EEG signals. The researchers also addressed problems with brain death and other neurological disorders, such as coma, in addition to epilepsy. Here are a few more important applications of EEG analysis in BCI. This is a very powerful and efficient method of communication between the human brain and the computer. The full literature review is divided into four sections:

## 2.1 Epilepsy detection using Deep learning Approach

Kunekar, P. et al. (2024) [1] This study introduces and contrasts deep learning and machine learning techniques for automated epileptic seizure identification. The UCI-Epileptic Seizure Recognition dataset serves as both the training and validation dataset. Some of the conventional ML and DL approaches are merged with a proposed model that utilizes long short-term memory (LSTM) to identify the best course of action. The best technique for identifying epileptic episodes is then ascertained by comparing several algorithms. With a 97% validation accuracy, the proposed model LSTM produces the most suitable and accurate results when compared to the other algorithms covered in this study.

Ahmad Ijaz, et al. (2022) [3] This work attempts to fill a research gap by conducting a comprehensive systematic evaluation of the latest developments in EEG-based ML/DL technologies for epileptic seizure identification. In relation to EEG-based epileptic seizure detection, the paper closely analyzed and contrasted the effectiveness, limitations, and basic challenges of a number of statistical feature extraction methods, ML/DL models, and recent developments in seizure identification. Additionally, acceptable standards for selecting

appropriate and successful feature extraction techniques and ML/DL models for epileptic seizure diagnosis were also discussed. The study's insights will assist researchers pick the best ML/DL models with the best feature extraction approaches to boost the efficacy of EEG-based epileptic episode diagnosis.

A range of screening techniques have been put forth to diagnose epileptic seizures using magnetic resonance imaging (MRI) and electroencephalography (EEG) modalities, according to Shoeibi et al. (2021) [4]. Deep learning (DL) is one of the many subfields of artificial intelligence. Prior to the emergence of DL, features were extracted using conventional machine learning techniques. As a result, they were only as good as the people who made the features by hand. However, both feature extraction and classification are fully automated by DL. The diagnosis of epileptic seizures is one of the medical professions that has considerably profited from these procedures.

According to Hussein Ramy et al. (2018) [5], epilepsy is the second most common brain disorder after migraines. Automatic detection can greatly improve the quality of life for patients with epileptic seizures. Current electroencephalogram (EEG)-based seizure detection techniques have several practical challenges. EEGs are non-stationary signals, and the patterns of seizures vary from person to person and between recording sessions. Furthermore, the accuracy of identifying epileptic seizures in EEG data may be impacted by a wide variety of noise types. To solve these challenges, we provide a deep learning-based approach that automatically detects the discriminative EEG features of epileptic episodes. To illustrate the connection between succeeding data samples, the time-series EEG data are specifically first split into a number of non-overlapping epochs. Second, an LSTM network is used to learn the high-level representations of the normal and epileptic EEG signals. Third, these representations are passed to the Softmax function for training and classification. The results on a well-known benchmark clinical dataset demonstrate how much superior the proposed approach is to the state-of-the-art methods at the moment. Furthermore, our approach is shown to be robust in noisy and real-world settings. In contrast to current methods that are extremely susceptible to noise, the proposed method maintains its excellent detection performance even in the presence of common EEG artifacts (muscle activity and eye-blinking) and white noise.

Abdelhameed et al. (2021) [6] The electroencephalogram (EEG) is one of the most crucial instruments used by doctors to identify seizures and other neurological conditions of the

human brain. Given the distinctive characteristics of epileptic seizures and the subsequent negative effects they have on patients' quality of life, a precise diagnosis of epilepsy is crucial. This paper suggests a novel deep-learning method based on the categorization of minimally pre-processed raw multichannel EEG signal recordings for the purpose of detecting seizures in children.

Two effective techniques for automated seizure diagnosis in EEG recordings were used by Jaiswal AK et al. (2017) [7]: cross-subpattern correlation-based PCA (SubXPCA) using Support Vector Machine (SVM) and subpattern-based PCA (SpPCA). To extract features, SpPCA and SubXPCA were employed. Both techniques look at the subpattern correlation of the EEG signals, which helps in decision-making. SVM is used to distinguish between seizures and non-seizures in EEG recordings. All experiments utilized the benchmark EEG dataset for epilepsy. There are 500 EEG signals in the entire dataset, all of which were recorded under different circumstances. Seven different experimental cases have been conducted for classification. The classification accuracy was evaluated using tenfold cross-validation. The categorization results of the proposed approaches have been compared with those of a few other approaches published in the literature in order to bolster the claim.

Uyttenhove, Thomas, et al. (2020) [8] The authors proposed the first deep learning approach and the second machine learning approach in general for the latter goal. Additionally, it does so in an understandable manner to validate the proposed method for wider application in medical care and maybe to find unknown epileptic biomarkers. The Tiny Visual Geometry Group (t-VGG) convolutional neural network is evaluated using a set of variable-length EEG recordings taken during routine exams, called the EEG Epilepsy Corpus. With an Area Under the Precision-Recall Curve (AUPR) of 93.02 for epileptic predictions and 55.85 for healthy ones, the t-VGG network significantly improved the accuracy of individual 10-second EEG window predictions. Additionally, by averaging window predictions each recording, the t-VGG's corresponding AUPR results were improved to 95.52 and 77.27.

Deivasigamani et al. (2023)[9] proposed an automatic identification and diagnosis of EEG data for epilepsy condition using soft computing techniques such as neural networks (NN) and adaptive neuro-fuzzy inference system (ANFIS). The following characteristics are taken from the decomposed coefficients in order to categorize EEG signals into focal and non-focal signals for the diagnosis and detection of epilepsy: skewness (S), kurtosis (K), entropy (E), activity feature (AF), mobility feature (MF), complexity feature (CF), skewness (B),

and weight feature (W). Focus signals are detected using ANFIS classifiers, and their severity levels are diagnosed using NN classification algorithms. The proposed method is used for several clinical problems.

Mohamed Sami and Nafea. (2022)[10] This work aims to give a comprehensive overview of the main challenges in the field of seizure detection, prediction, and classification using EEG data, along with the methods employed to overcome these challenges using ML and DL approaches. The main findings of the review are summarized, and some important concepts regarding the use of deep learning and machine learning to seizure categorization, prediction, and detection are discussed in further detail. This study aims to better understand the many approaches for identifying the different forms and stages of epileptic seizures in order to help experts in the field and enhance the lives of future epileptic patients.

Antoniades et al. (2016)[11] This work proposes utilizing deep learning to automatically create characteristics from time-domain epileptic intracranial EEG data. Specifically, demonstrate that convolutional neural networks (CNNs) automatically learn significant characteristics that represent IEDs by taking a subject-independent look at them. The resultant model delivers state-of-the-art classification performance, provides insights into the different types of IEDs within the group, and is invariant to temporal disparities between the IEDs. This work suggests that automated feature creation based on deep learning is suitable for both IEDs and EEG in general.

According to Poorani et al. (2023)[12], two different DL models are used for patient-specific seizure detection using CHB-MIT data; the outcomes are better than those of the existing DL model. The first model focuses on the one-dimensional CNN, whereas the second model focuses on the CNN + LSTM hybrid architecture. 94.5% is the F1-score, 0.5 is the FPR, 0.9 is the FNR, 90 is the MCC, 94.83% is the prediction accuracy, 90.18% is the sensitivity, 99.48% is the specificity, and 99.43% is the precision for 11 epochs. In the end, it has been shown that these two models function differently for different patients.

Ayesha et al. (2021)[13] concentrate on determining the most unique and discriminating features of seizure EEG recordings in order to develop a technique that employs both fuzzy-based and traditional machine learning algorithms for epileptic seizure diagnosis. The proposed framework classifies unknown EEG signal segments into ictal and interictal groups. The model is validated empirically using two benchmark datasets: the Children's

Hospital of Boston-Massachusetts Institute of Technology (CHB-MIT) dataset and the Bonn dataset. The findings show that K-Nearest Neighbour (KNN) and Fuzzy Rough Nearest Neighbour (FRNN) offer the highest percentages of sensitivity and specificity as well as the greatest classification accuracy scores in both scenarios.

In Acharya et al. (2018)[15], a computer-aided diagnosis (CAD) system that can automatically determine the type of these EEG data is developed using machine learning techniques. This is the first research to use a convolutional neural network (CNN) to interpret EEG data. This study used a 13-layer deep convolutional neural network (CNN) approach to distinguish between the normal, preictal, and seizure classes. The recommended method's sensitivity, specificity, and accuracy were 95.00%, 90.00%, and 88.67%, respectively.

Hossain et al. (2019)[16] suggested a deep CNN model for seizure detection tasks using an open-access EEG epilepsy dataset collected at Boston Children's Hospital. In order to understand the overall structure of a seizure that is less susceptible to fluctuations, the deep learning model can extract spectral and temporal information from the EEG epilepsy data. Using cross-patient EEG data from 23 patients, our method produced an overall sensitivity of 90.00%, specificity of 91.65%, and accuracy of 98.05%. The system has a 99.46% seizure detection accuracy. It is therefore an excellent cross-patient seizure classifier. The results show that our model outperforms the previous state-of-the-art techniques for seizure detection tasks that are both patient-specific and cross-patient. For patient-specific data, the method's overall accuracy was 99.65%. The device may also see the orientation of the distinctive band power characteristic. We use correlation maps to connect spectral amplitude characteristics to the output in the form of images. According to the results of our deep learning model, this visualization method may be used as a potent multimedia tool to provide quick and relevant brain mapping pictures that researchers can use.

By employing Long Short-Term Memory (LSTM) networks in the prediction of epileptic seizures using EEG inputs, Tsiouris et al. (2018)[17] expand on the use of deep learning techniques with convolutional neural networks (CNN). The evaluation shows that the proposed methodology can predict all 185 seizures with high seizure prediction sensitivity and low false prediction rates (FPR) of 0.11 to 0.02 false alarms per hour, depending on the length of the preictal window, using long-term EEG recordings from the publicly available CHB-MIT Scalp EEG database. The proposed LSTM-based approach considerably

enhances seizure prediction abilities in comparison to convolutional neural networks and other machine learning techniques evaluated in the literature.

M. In order to determine the probability of epileptiform discharges, C. Clostermans-Tjepkema et al. (2018)[18] employed a variety of convolutional and recurrent neural network combinations. The network with the largest area under the ROC curve (AUC) in the test set was validated using seven distinct EEGs with focal epileptiform discharges and twelve normal EEGs. The final network's AUC for the test set was 0.94. Following validation, epileptiform discharges were found with 98.0% specificity and 47.4% sensitivity (FPR: 0.6/min). The specificity of the normal EEGs in the validation set was 99.9% (FPR: 0.03/min).

Savadkoohi et al. (2020)[19] This study looks at the features of the electrical activity in the brain from different recording sites and physiological circumstances in order to identify seizures. Neurophysiologists will benefit from the findings by being able to quickly and reliably diagnose epileptic episodes in their patients. We looked into the best technique for seeing important patterns in an epileptic patient's electroencephalogram (EEG).

Neurologists use visual analysis of electroencephalogram (EEG) data to diagnose epilepsy (Yuan et al., 2022)[20]. However, researchers have proposed automated methods to make the diagnosis due to the time-consuming procedure and worldwide lack of professionals. Machine learning techniques have been used in the majority of recent studies. However, some groups are already working on deep learning methods for computer-aided diagnostic (CAD) systems. The authors of this research suggest a long short-term memory (LSTM) and convolutional neural network (CNN) model for seizure detection.

Miltiadous et al. (2020)[21] It provides a comprehensive examination of the signal processing and classification methods used to the different datasets and provides useful data for additional study. The investigations were analyzed using the categorization strategy, evaluation database, and Signal Transformation technology. Among other things, Convolutional Neural Networks that integrate Time-Frequency decomposition of pictures are increasingly being used.

Using classifier algorithms (K-Nearest Neighbours (Knn), Support Vector Machine (SVM), Random Forest (RF), and Long Short-Term Memory (LSTM), Tuncer et al. (2022)[22]

include preprocessing scalp electroencephalogram (EEG) data, feature extraction using the discrete wavelet method, feature selection using the correlation-based feature selection (CFS) method, and data classification using these techniques. Following the application of the proposed technique to 23 individuals in the Temple University Hospital (TUH) scalp EEG data set, the deep learning architecture LSTM effectively obtained a classification success rate of 95,92% for case (I) and 98,08% for case (II).

A novel machine learning-based technique for detecting epileptic seizures in EEG recordings is introduced by Tran et al. (2022)[23]. A publicly accessible EEG dataset from the University of Bonn was used to validate the approach. Meaningful statistical characteristics were extracted from the original data using discrete wavelet transform analysis, and the relevant features were selected using feature selection based on the binary particle swarm optimizer. The results showed that, with an accuracy of up to 98.4%, the recommended method was very effective and helpful in detecting the presence of seizures in EEG data. This strategy may alleviate the strain on neurologists and the agony of epileptic patients in clinical settings.

Malekzadeh et al. (2021)[24] This study presents a computer-aided diagnostic system (CADS) for automatically identifying epileptic episodes in EEG data. The proposed technique consists of three steps: classification, feature extraction, and preprocessing. The simulations are performed using the Bonn and Freiburg datasets. When the recovered attributes were input into the proposed CNN–RNN model, satisfactory results were achieved. The K-fold cross-validation with k = 10 is employed in the classification stage to demonstrate the effectiveness of the proposed CNN–RNN classification procedure. The results showed that the proposed CNN–RNN method has an accuracy of 99.71% for the Bonn dataset and 99.13% for the Freiburg dataset.

According to Usman et al. (2020)[25], epilepsy is a neurological condition that affects more than 65 million individuals globally. In over 30% of instances, neither medication nor surgery can cure the ailment. However, by taking therapeutic action in advance of a seizure, it can be prevented. Research indicates that the preictal state, a period of aberrant brain activity, starts a few minutes before a seizure really starts. It is still difficult to predict this preictal condition of a seizure with high sensitivity and specificity, despite several attempts by researchers. The proposed seizure prediction system in this study makes use of deep learning techniques. Preprocessing scalp EEG data, automated feature extraction,

convolution neural network use, and classification using vector machine assistance are all included in this method.

Effective techniques for categorizing EEG signals for ictal, pre-ictal, and normal activities are proposed by Ibrahim et al. (2022) [26]. For the categorization task, three models are displayed. In contrast to the other two, which are patient-specific, the third one is patient non-specific, making it more appropriate for general categorization tasks. A two-class classification between normal and ictal activities is employed for seizure detection, and between normal and pre-ictal activities for seizure prediction. A more comprehensive three-class categorization approach is considered in order to identify all EEG signal activity.

According to Siddiqui et al. (2020)[27], this study attempts to give an overview of the wide variety of approaches that have been developed in recent years based on the classification of statistical characteristics and machine learning classifiers, which are categorized as "black-box" or "non-black-box." The state-of-the-art methods and concepts that are being presented will give a thorough understanding of seizure detection and classification, as well as future research possibilities.

Jana and others. convolutional neural network (CNN) using channel minimization as an efficient seizure prediction technique (al., 2021)[28]. CNN has been used to categorize the states of epileptic patients and automatically extract characteristics. An average classification accuracy of 99.47 percent (≈100 percent) may be achieved by optimizing the EEG channels to 6 from 22, or 72.73 percent of the total number of channels. The recommended method has a false positive rate of 0.0764 and average sensitivity and specificity of 97.83% and 92.36%, respectively.

Akut et al. (2019)[29] claim that this approach is incongruous as it employs complex characteristics to identify epilepsy. To tackle this problem, we have created a wavelet-based deep learning approach that outperforms the state-of-the-art machine learning methods on a significantly smaller number of datasets and does not need feature extraction. To evaluate the robustness of our model, we applied it to a binary (2-way) and ternary (3-way) classification.

Natu et al. (2022)[30] This paper presents many approaches based on various attributes and classifiers throughout the previous few years. The methods covered will give a

comprehensive understanding of seizure prediction and ideas for further study.

C. Lee H. The literature on deep learning (DNN, RNN, CNN, and so on) for analyzing EEG data in order to interpret brain activity and detect diseases was reviewed by et al. (2020)[31]. In order to help readers understand the differences between CNN and RNN, they also included information on various topologies. It looked at a phrase that provided a CNN and LSTM-based model and showed how these methods might be used to optimize and set up a deep learning architecture's hyperparameters.

**Table 2.1: Comparative Analysis of different Approaches**

| S. No. | Author | Publisher and Year | Technology Used and Findings | Limitations |
|---|---|---|---|---|
| 1 | Muhammad, Nazeer, et al | Elsevier, 2018 | AlexNet and VGG19 CNNs used for classifying EEG signals into seizure and non-seizure states with high accuracy. | Computationally expensive and requires a large dataset for proper model training. |
| 2 | Bhagat and Monu, et al | Springer, 2021 | Support Vector Machine with Grid Search methodology achieved improved classification for epileptic seizure detection. | Performance drops significantly with noisy or unbalanced datasets. |
| 3 | Shruthi, U and V. Nagaveni et.al | MDPI, 2022 | Five different machine-learning classification approaches compared for seizure detection, with Random Forest showing the best results. | Limited generalizability due to dataset constraints. |
| 4 | Froldi, Guglielmina, et al | Wiley Online Library, 2020 | Analyzed the use of recurrent neural networks for predicting epileptic seizures in interictal EEG data. | RNNs showed difficulties in processing longer sequences due to vanishing gradient issues. |
| 5 | Babu, Spoorthy N. et.al | IEEE Access, 2019 | Convolutional Neural Networks (CNNs) applied for epilepsy detection demonstrated enhanced accuracy in | Does not effectively address class imbalance in datasets. |

| | | | | |
|---|---|---|---|---|
| | | | real-time applications. | |
| 6 | Gauri Deshpande and Pratiksha Shinde et.al | Frontiers in Neuroscience, 2021 | Hybrid approach using deep learning and statistical analysis to classify seizure types. | Model complexity limits its deployment on low-resource devices. |
| 7 | Ahmad, I., Wang, X., et al | MDPI, 2022 | Systematic review of machine and deep learning approaches for EEG-based epileptic seizure detection. | Lack of robust datasets for validation and retracted data concerns. |
| 8 | Shoeibi, A., et al | MDPI, 2021 | Comparative review of deep learning techniques for automated seizure detection. | Over-reliance on specific datasets limits the applicability of findings. |
| 9 | Hussein, R., et al | arXiv, 2018 | Focused on the use of labeled EEG datasets for seizure detection via deep learning approaches. | Dataset dependency and lack of real-time system implementation. |
| 10 | Abdelhameed, A., et al | Frontiers in Computational Neuroscience, 2021 | Deep learning approach optimized for pediatric epilepsy using multichannel EEG data. | Challenges in scaling the approach for different age groups and conditions. |
| 11 | Jaiswal, A. K., and Banka, H. | Springer, 2018 | Machine learning-based seizure detection using EEG signals with a focus on statistical feature extraction. | Limited exploration of deep learning techniques. |
| 12 | Uyttenhove, T., et al | Machine Learning Research, 2020 | Focused on interpretable models for seizure detection in interictal EEG data using deep learning. | Interpretability trade-offs with accuracy in some instances. |
| 13 | Deivasigamani, S., et al | Springer, 2021 | Neuro-fuzzy inference systems for EEG-based epilepsy detection. | Limited testing across diverse datasets. |
| 14 | Nafea, M. S., and Ismail, Z. H. | MDPI, 2022 | Supervised ML and DL techniques used for automated epilepsy recognition via EEG signals. | Heavy reliance on handcrafted features for some methodologies. |
| 15 | Antoniades, A., et al | IEEE, 2016 | Explored multilayer feature learning for intracranial EEG data | Limited exploration of transfer learning approaches. |

| | | | | |
|---|---|---|---|---|
| | | | using deep learning. | |
| 16 | Poorani, S., et al | Springer, 2023 | Combined CNNs with patient-specific optimization to enhance detection rates in EEG data. | Generalizability issues across patient populations. |
| 17 | Aayesha, M. B., et al | Springer, 2021 | Used SVMs and ML classifiers for EEG-based seizure classification. | Model struggles with noisy or incomplete datasets. |
| 18 | Rasheed, K., et al | IEEE Reviews in Biomedical Engineering, 2020 | Comprehensive review of EEG-based seizure prediction with ML methods. | Focuses primarily on feature engineering, with less emphasis on end-to-end learning models. |
| 19 | Acharya, U. R., et al | Elsevier, 2018 | Deep CNNs for automated EEG signal classification into normal, preictal, and seizure categories. | Computational cost and hardware requirements. |
| 20 | Hossain, M. S., et al | ACM Transactions, 2019 | Combined deep learning and brain mapping visualization for epilepsy detection. | Limited to specific datasets without broader validation. |
| 21 | Tsiouris, K. M., et al | Elsevier, 2018 | LSTM-based networks for long-term prediction of epileptic seizures. | LSTM performance affected by data imbalance and noise. |
| 22 | Tjepkema-Cloostermans, M. C., et al | Elsevier, 2018 | Deep learning applied to focal epileptiform discharge detection in scalp EEG recordings. | Focused mainly on a limited dataset, reducing generalizability. |
| 23 | Savadkoohi, M., et al | Elsevier, 2020 | KNN and SVM-based methods for EEG-based seizure prediction. | Limited testing on real-world noisy datasets. |
| 24 | Yuan, Y., et al | IEEE, 2018 | Multi-view deep learning framework for EEG seizure detection incorporating frequency and time-domain features. | High computational complexity during training phases. |
| 25 | Miltiadous, A., et al | IEEE Access, 2022 | Systematic review of ML algorithms for epilepsy detection using public EEG | Few guidelines for clinical adaptation of the proposed methods. |

| | | | | |
|---|---|---|---|---|
| | | | databases. | |
| 26 | Tuncer, E., et al | Elsevier, 2022 | Single-channel EEG analysis for seizure type classification using ML techniques. | Limited scalability for multi-channel EEG systems. |
| 27 | Tran, L. V., et al | MDPI, 2022 | Machine learning-based approaches for non-seizure and seizure EEG classification. | High dependence on feature selection techniques. |
| 28 | Malekzadeh, A., et al | MDPI, 2021 | CNN-RNN hybrid models for EEG-based epilepsy detection. | Computational inefficiencies in training and prediction phases. |
| 29 | Usman, S. M., et al | IEEE Access, 2020 | Investigated DL-based methods for seizure prediction using scalp EEG data. | Limited evaluation under real-time conditions. |
| 30 | Ibrahim, F. E., et al | Wiley, 2022 | Explored deep-learning-based EEG seizure detection and prediction using medical data. | Ethical concerns in patient data handling and model explainability. |

## 2.2 Overall Common Findings

- Data Dependency: All methodologies heavily depend on the quality and quantity of EEG data. Consistent data collection, preprocessing, and augmentation can significantly improve model outcomes.
- Interdisciplinary Approach: A successful application requires an interdisciplinary approach, combining expertise from neurology, data science, and computational neuroscience.
- Customization: There's no one-size-fits-all solution. Models often need to be customized based on the specifics of the EEG dataset and the characteristics of the epileptic events being studied.
- Evolution: The field is rapidly evolving, with new algorithms and techniques being developed. Continual learning and updating of methodologies are essential for maintaining state-of-the-art performance.

The detection of epileptic events through electroencephalogram (EEG) recordings remains a pivotal endeavor in medical research. As neurology intersects with the computational world, the use of Machine Learning (ML), Deep Learning, and Artificial Neural Networks (ANNs) in this context is increasingly advocated. This synthesis aims to provide theoretical support for the strengths, weaknesses, and common findings outlined in our previous analysis of this critical intersection of technology and medicine.

## 2.3 Research Gaps

- Insufficiency in Existing Preprocessing Techniques: Current preprocessing techniques for EEG signals may not effectively reduce noise and artifacts, thus possibly compromising the accuracy of epilepsy detection.

- Inadequate Feature Engineering: Existing feature engineering methodologies might not capture all the relevant characteristics of epileptic EEG signals, leading to suboptimal classification outcomes.

- Limitations in Classification Approaches: Many EEG classification methodologies in use today might not efficiently classify epileptic and non-epileptic signals, necessitating a thorough review of available techniques.

- Gap in Soft Computing Application: While machine learning techniques have been applied for EEG signal classification, soft computing methods, which may offer additional benefits, might not have been extensively studied.

- Suboptimal Hyperparameter Tuning: Many machine learning models for EEG classification might be working suboptimally due to inadequate hyperparameter tuning, thereby missing out on possible accuracy improvements.

- Lack of Transfer Learning Application: Current models might not make the best use of transfer learning, thereby not leveraging knowledge from related domains or tasks which could enhance performance.

- Limited Model Comparisons: There's a potential lack of comprehensive studies comparing the performance of various models on a diverse range of patient data, leading to uncertain generalization capabilities.

- Non-diversified Patient Data: Many models might be trained and tested on homogeneous patient data, which can lead to overfitting and reduced applicability in real-world scenarios.

- Lack of Holistic Model Analysis: Existing studies might not look at models from an end-to-end perspective, considering both preprocessing, feature engineering, and classification simultaneously, which could uncover potential performance bottlenecks.

- Scalability Concerns: With the surge in EEG data being generated, current methodologies might not be scalable to handle large datasets, demanding innovative approaches that can process vast amounts of data efficiently.

# 3. PRESENT STUDY

The proposed study delves into the advanced methodologies for the classification and detection of epileptic seizures using electroencephalogram (EEG) signals. The integration of machine learning and deep learning frameworks into biomedical signal processing forms the backbone of this research.

## 3.1 Overview of Epileptic Seizure Detection

Epileptic seizures represent a neurological anomaly that necessitates accurate, timely detection for effective management. EEG signals, capturing the brain's electrical activity, have emerged as a cornerstone diagnostic tool. Despite their potential, challenges such as artifacts, variability in signal patterns, and inter-patient differences hinder consistent diagnosis. These obstacles underscore the necessity for robust computational models capable of analyzing EEG data with precision.

## 3.2 Research Objectives

- To evaluate and explore effective preprocessing and classification techniques for detecting and classifying epilepsy from EEG signals.
- To examine and assess improved machine/deep learning-based classification systems for identifying epileptic seizures using EEG data.
- To design and evaluate a robust classification model utilizing improved multiple model approach.
- To assess and compare the performance of the proposed model using diverse patient datasets for thorough analysis and validation.

### 3.3 EEG Data

EEG data presents both opportunities and challenges. The signals provide granular insights into brain activity, particularly in identifying seizures. However, they are highly susceptible to artifacts from external and internal factors, such as eye blinks and muscle contractions. This research adopts a twofold approach:

- **Data Preparation**: A rigorous preprocessing phase to enhance signal clarity and reduce noise.
- **Feature Selection**: Extracting meaningful features for classification, balancing computational efficiency and accuracy.

## 3.4 Novel Contributions

The proposed study introduces a hybrid CNN-RNN model, leveraging the strengths of both architectures. While CNNs excel in spatial feature extraction, RNNs are adept at capturing temporal dependencies. This combination addresses limitations observed in standalone models.

- **End-to-End Learning**: Automation of feature extraction and classification, reducing dependency on manual interventions.
- **Artifact Mitigation**: Enhanced preprocessing techniques to tackle artifacts, ensuring cleaner input data.
- **Generalization**: Validation on diverse datasets to ensure model applicability across varying patient demographics.

## 3.5 Anticipated Outcomes

- A robust hybrid model surpassing traditional methods in accuracy and reliability.
- Comprehensive insights into feature importance, aiding interpretability and clinical application.
- A scalable framework adaptable to different EEG datasets and clinical environments.

# 4. METHODOLOGY

## 4.1 Research Flow Diagram

The classification and detection of epileptic EEG signals is a crucial topic in biomedical signal processing. Machine learning (ML) provides a powerful set of tools to address this problem. Here's a step-by-step breakdown of the process, from data acquisition to model evaluation.

### 4.1.1 Data Acquisition

- EEG Signals: These are electrical recordings of the brain activity captured using electrodes placed on the scalp. For epilepsy detection, data from both healthy individuals and epilepsy patients are needed.




Figure 4.1: Data Acquisition

### 4.1.2 Pre-processing

Before feeding EEG data to any machine learning model, it needs to be cleaned and pre-processed.

- Filtering: Remove noise from the EEG data using band-pass filters, typically focusing on frequencies between 0.5-70 Hz.
- Artifact Removal: Common artifacts in EEG data include eye movements, muscle activity, and line noise. Independent Component Analysis (ICA) and Wavelet-based methods are popular for artifact removal.




Figure 4.2: Pre-processing of Data

### 4.1.3 Segmentation

Divide the continuous EEG data into smaller epochs or segments, usually ranging from 1-5 seconds. The goal is to classify each segment as epileptic or non-epileptic.

### 4.1.4 Feature Extraction

Extracting meaningful features from EEG segments is crucial for efficient classification.

- Time-Domain Features: These include statistical measures like mean, variance, skewness, and kurtosis of the EEG segment.
- Frequency-Domain Features: Power spectral density (PSD), relative power in specific EEG bands (Delta, Theta, Alpha, Beta, Gamma).
- Time-Frequency Features: Wavelet transform coefficients or spectrogram-based features capture both time and frequency information.
- Nonlinear Features: Lyapunov exponents, entropy measures, and fractal

dimensions are used to capture the nonlinear nature of EEG signals.




Figure 4.3: Feature Extraction

### 4.1.5 Feature Selection

With hundreds of potential features, it's essential to select the most informative ones.

- Statistical Tests: F-tests, chi-squared tests, and mutual information can rank features based on their discriminative power.
- Recursive Feature Elimination (RFE): Uses a model (like SVM) to rank features based on their contribution to classification performance.
- Regularization Techniques: Lasso or Ridge regression can inherently perform feature selection.

### 4.1.6 Model Training

Various ML algorithms can be used, but the following are popular for EEG classification:

- Support Vector Machines (SVM): Good for binary classification problems.
- Random Forest: Handles non-linear data well and provides feature importance metrics.

- Convolutional Neural Networks (CNN): Especially when using raw EEG data or spectrograms.
- Recurrent Neural Networks (RNN): Useful for capturing temporal dependencies in EEG data.

### 4.1.7 Model Evaluation

Using hold-out validation data, evaluate the model's performance.

- Metrics: Accuracy, Sensitivity, Specificity, Area under the ROC curve (AUC).
- Cross-validation: To ensure the model's robustness, use k-fold cross-validation.




Figure 4.4: Model Evaluation

### 4.1.8 Post-processing

Sometimes, post-processing steps like majority voting (if the majority of consecutive segments are detected as epileptic, then it's labeled as an epileptic event) are used to refine the results.

The application of machine learning & Deep learning for detecting and classifying epileptic EEG signals represents a fascinating intersection of healthcare and technology. The journey from data acquisition to deployment is complex, but with the right steps, tools, and considerations, machine learning can significantly enhance the efficiency and accuracy of epilepsy diagnosis and monitoring. The field is rapidly evolving, with advances in deep learning, data availability, and computational techniques providing opportunities for even more effective solutions in the future.

# 5. DATA ANALYSIS/DISCUSSION

Epileptic seizures, characterized by abnormal brain activity, represent one of the most challenging neurological disorders to diagnose and monitor. Electroencephalogram (EEG) recordings serve as a critical tool in detecting and analyzing these seizures, providing real-time insights into brain activity. The datasets from Bonn University and the MIT CHB-MIT Scalp EEG database are widely utilized for advancing research in epilepsy detection and classification. This section delves into the characteristics of these datasets, the preprocessing techniques employed, the feature extraction methodologies, and general insights derived from these studies.

## 5.1 Overview of EEG Datasets

### 5.1.1 Bonn University Dataset

The Bonn University dataset [58] is a benchmark in epilepsy research. It consists of five subsets labeled A, B, C, D, and E. These subsets reflect a progression of brain activity from healthy individuals to epileptic seizures. The data is captured at a sampling rate of 173.61 Hz and recorded using a 128-channel EEG amplifier.

- **Healthy Activity (A and B)**: These subsets represent EEG signals from healthy individuals under different conditions—eyes open (A) and eyes closed (B).
- **Interictal States (C and D)**: These subsets capture non-seizure activity in epilepsy patients.
- **Ictal States (E)**: This subset records brain activity during seizures.

The Bonn dataset is particularly valuable due to its well-segmented and clearly labeled data, which facilitates feature extraction and model training.

### 5.1.2 MIT CHB-MIT Dataset

The CHB-MIT Scalp EEG dataset [59] is more complex, offering long-term EEG recordings from pediatric patients. This dataset captures a wide range of seizure and non-seizure events and is recorded at a higher sampling rate of 256 Hz.

- **Patient Diversity**: It includes data from over 20 patients, each with unique seizure patterns, inter-patient variability, and distinct EEG characteristics.
- **Clinical Relevance**: The dataset provides real-world complexity, including artifacts from patient movement, muscle activity, and other sources.
- **Extended Recordings**: Each recording spans several hours, often containing multiple seizure events.

This dataset is particularly suited for studying the temporal evolution of seizures and the impact of variability across patients.

## 5.2 Data Preprocessing

Preprocessing is a critical step in preparing EEG data for analysis. Raw EEG recordings are often contaminated with noise and artifacts, which can obscure the patterns associated with epileptic seizures. Both datasets underwent rigorous preprocessing to enhance signal quality and ensure meaningful analysis.

**Noise Reduction:** Noise in EEG data primarily originates from electrical interference, low-frequency drift, and high-frequency noise. Band-pass filters were applied to retain frequencies within the 0.5–70 Hz range, which encompasses most relevant brain activity.

**Artifact Removal:** EEG signals are prone to artifacts from sources such as eye movements (EOG), muscle activity (EMG), and cardiac signals (ECG). Techniques like Independent Component Analysis (ICA) and wavelet transforms were used to isolate and remove these artifacts.

- **EOG Artifacts**: Characterized by large amplitude and low frequency, these artifacts were identified and removed using ICA.
- **EMG and ECG Artifacts**: High-frequency components associated with muscle activity and cardiac rhythms were suppressed using wavelet-based methods.

**Segmentation:** Continuous EEG recordings were segmented into fixed-length epochs, typically ranging from 1–5 seconds. This segmentation facilitates localized analysis of seizure and non-seizure events, making the data suitable for feature extraction and classification.

**Normalization:** To ensure consistency across different recordings, EEG signals were normalized to standardize amplitude and eliminate bias caused by variations in recording conditions.

## 5.3 Feature Extraction

Feature extraction transforms raw EEG signals into a structured format suitable for machine learning models. The Bonn and MIT datasets enabled the exploration of diverse features, each capturing unique aspects of brain activity.

**Time-Domain Features:** Time-domain features characterize statistical properties of EEG signals within an epoch. These include:

- **Mean and Variance**: Provide insights into the central tendency and variability of the signal.
- **Skewness and Kurtosis**: Measure the asymmetry and peakedness of the signal distribution.
- **Zero-Crossing Rate**: Indicates the frequency of signal polarity changes, often elevated during seizures.

**Frequency-Domain Features:** Frequency-domain features, derived from power spectral analysis, highlight the distribution of energy across different frequency bands:

- **Delta (0.5–4 Hz)**: Dominates during deep sleep and indicates slow-wave activity.
- **Theta (4–8 Hz)**: Associated with drowsiness and relaxation.
- **Alpha (8–13 Hz)**: Reflects calmness and mental relaxation.
- **Beta (13–30 Hz)**: Linked to active thinking and problem-solving.
- **Gamma (>30 Hz)**: Represents high-frequency oscillations observed during seizures.

**Time-Frequency Features:** Wavelet transforms provided a comprehensive representation of EEG signals by capturing both time and frequency information. This method proved particularly effective in isolating transient seizure patterns.

**Nonlinear Features:** EEG signals exhibit nonlinear characteristics due to the brain's complex neural dynamics. Features like Lyapunov exponents, entropy measures, and fractal dimensions captured these complexities, offering additional discriminative power for seizure detection.

## 5.4 Summary

The analysis of EEG data from the Bonn and MIT datasets underscores the potential of advanced preprocessing and feature extraction techniques in enhancing seizure detection. While challenges persist, the integration of machine learning and deep learning frameworks offers a promising path forward. By addressing issues such as inter-patient variability, artifact contamination, and scalability, future research can pave the way for more accurate and reliable epilepsy diagnostic systems. This journey represents a pivotal intersection of neuroscience, signal processing, and computational intelligence, promising significant advancements in patient care and medical research.

# 6. CONCLUSION

## 6.1 Conclusion

The application of machine learning (ML) techniques has revolutionized the field of biomedical engineering, especially in the processing and interpretation of EEG data for epilepsy detection. The following sections summarize the importance, approaches, and difficulties associated with this multidisciplinary project. The lives of those who suffer from epilepsy, a neurological condition marked by recurrent seizures, are significantly impacted. Treatment plans are informed by fast and accurate detection utilizing EEG recordings, which also helps with diagnosis. Machine learning is a powerful method to increase the accuracy of epilepsy detection from EEG signals because of its capacity to identify patterns in large datasets.

The electrical activity of the brain is reflected in an EEG signal, which is frequently distorted by noise and distortions. Pre-processing is a fundamental step that guarantees the best quality data is supplied into machine learning algorithms. Filtering, segmentation, and artifact removal are among techniques that improve the signal quality and make it appropriate for additional analysis. In addition to improving downstream job accuracy, properly pre-processed data lowers computing overheads. In both the temporal and frequency domains, certain patterns or characteristics frequently contain the essence of an EEG signal. These characteristics are condensed using feature extraction techniques, which yield a clear illustration. While frequency-domain qualities show the power distribution across various frequency bands, time-domain features capture the statistical subtleties of the signals. Both realms are bridged by time-frequency studies, including the wavelet transform, which provide a fine-grained understanding of signal dynamics. Conversely, nonlinear aspects highlight the subtleties of the EEG signals and frequently resonate with the intricate, non-linear structure of brain activity. Machine learning techniques are used once the features have been retrieved and chosen. With their own advantages, models like Support Vector Machines, Random Forests, and Neural Networks have all been used widely. Deep learning models, especially Convolutional Neural Networks, are incredibly effective yet data-hungry because they can automatically extract features, whereas standard techniques like SVM rely on human feature extraction. Models must be generalizable over a variety of patient cohorts due to the inter-patient heterogeneity in EEG data. A common problem is overfitting, in

which models perform remarkably well on training data but poorly on unknown data. Additionally, a major worry is still the interpretability of ML models, particularly deep learning architectures. In the crucial field of healthcare, knowing the reasoning behind a model's forecast is just as important as the prediction itself. Additionally, data security and privacy are crucial, particularly in the era of cloud computing. Researchers and physicians must walk a tightrope between protecting patient privacy and utilizing machine learning's computing power. In conclusion, the intersection of neurology, signal processing, and machine learning embodies the collaborative future of healthcare. Supported by strong pre-processing and feature extraction, approaches for identifying epileptic episodes from EEG data have made encouraging progress. Despite ongoing difficulties, the interdisciplinary collaboration holds out hope for a time when epilepsy diagnosis would be both precise and prompt, signaling better clinical results and patient care. The journey of combining machine learning with EEG analysis is representative of the larger story: technology and healthcare working together to create a better future.

## 6.2 Challenges in Seizure Classification

EEG signals present several challenges in seizure classification, including:

- **Inter-Patient Variability**: Each patient’s brain exhibits unique patterns of electrical activity, meaning that the same type of seizure may look different across individuals.
- **Artifact Contamination**: EEG signals are prone to various artifacts caused by factors such as eye movement, muscle contractions, and even electrode malfunctions, which can distort the analysis and classification process.
- **Temporal Dynamics**: Seizures evolve over time, which means that a robust classifier must account for dynamic changes in the EEG signal across both time and frequency domains.
- **Imbalanced Datasets**: In many cases, the number of epileptic seizure events is much smaller than the number of non-epileptic seizure events, leading to class imbalance, which can bias traditional machine learning models.

# 7. WORK PLAN OF THE RESEARCH

### 7.1 Phase-1: Literature Survey (February 2025 – March 2025)

The first phase involves an extensive literature review to identify existing methods, trends, and research gaps in epileptic seizure detection using EEG signals. This step ensures that the research is grounded in current knowledge and addresses unaddressed challenges.

- **Activities**:
    - Reviewing articles, journals, and conference proceedings.
    - Identifying the strengths and weaknesses of existing EEG processing techniques.
    - Compiling key insights into a structured review.
- **Importance**:
    - Establishes the theoretical framework for the research.
    - Provides insights into which methods are worth exploring or improving.

### 7.2 Phase-2: Study of Existing Techniques (April 2025 – May 2025)

In this phase, existing EEG analysis techniques and algorithms are evaluated to determine their effectiveness in addressing epilepsy detection challenges. This includes analyzing traditional machine learning and deep learning approaches.

- **Activities**:
    - Comparing techniques such as SVM, CNN, and RNN.
    - Evaluating their ability to handle artifacts, inter-patient variability, and class imbalance.
    - Identifying strengths and weaknesses specific to each methodology.
- **Outcome**:

- The selection of potential approaches for further development.

### 7.3 Phase-3: GUI and Database Design (June 2025 – July 2025)

This phase focuses on designing a graphical user interface (GUI) and creating a comprehensive database for EEG data. The GUI will serve as a platform for visualizing and analyzing results, while the database will ensure efficient data storage and retrieval.

- **Activities**:
  - Designing the interface to display EEG signals, feature extraction, and classification results.
  - Setting up a database to manage EEG datasets from sources like the MIT CHB-MIT and Bonn University datasets.
  - Implementing functionality for preprocessing, segmentation, and annotation.
- **Significance**:
  - A well-designed GUI enhances usability for researchers and clinicians.
  - The database ensures data integrity and supports efficient data processing.


Gantt Chart for Proposed 22-Month Research Work Plan
Research Phases
Timeline (Months)
Phase-1 Literature Survey
Phase-2 Study of Existing Techniques
Phase-3 GUI and Database Design
Phase-4 Implementation and Algorithm Design
Phase-5 Testing and Performance Analysis
Phase-6 Validate Proposed Techniques
Documentation
0
1
2
3
4
5
6
Feb Mar Apr May Jun Jul Aug Sep Oct Nov Dec Jan Feb Mar Apr May Jun Jul Aug Sep Oct Nov Dec Jan Feb Mar

Figure 7.1: Work Plan of Proposed Research

### 7.4 Phase-4: Implementation and Algorithm Design (August 2025 – January 2026)

This is the core phase where the proposed hybrid deep learning framework is developed. The framework integrates CNNs for spatial feature extraction and RNNs for temporal pattern recognition, aiming to improve seizure detection accuracy.

- **Activities**:
    - Implementing preprocessing techniques such as wavelet transforms and ICA.
    - Designing and training the hybrid CNN-RNN model.
    - Conducting initial performance evaluations on the database.
- **Outcome**:
    - A functional model capable of analyzing EEG signals and classifying seizures effectively.

### 7.5 Phase-5: Testing and Performance Analysis (February 2026 – July 2026)

Once the model is developed, this phase is dedicated to rigorous testing and performance analysis. The model is evaluated using metrics such as accuracy, sensitivity, and specificity to ensure reliability.

- **Activities**:
    - Testing the model on diverse datasets to validate generalization.
    - Comparing the hybrid model with traditional approaches.
    - Fine-tuning hyperparameters to optimize performance.
- **Impact**:
    - Ensures the model is robust and applicable across various scenarios.

### 7.6 Phase-6: Validation of Proposed Techniques (August 2026 – October 2026)

The validation phase focuses on cross-checking the model's real-world applicability and scalability. Validation ensures the model’s reliability in handling unseen data and diverse patient profiles.

- **Activities**:
    - Applying the model to datasets with high variability.
    - Evaluating the model’s adaptability to different data sources.
    - Identifying any limitations or areas for improvement.
- **Outcome**:
    - A validated model ready for deployment in research or clinical settings.

### 7.7 Documentation (November 2026 – January 2027)

The final phase involves compiling the research findings into a comprehensive report. Documentation is crucial for disseminating the research to the scientific community.

- **Activities**:
    - Writing detailed sections on methodology, results, and analysis.
    - Preparing manuscripts for publication in journals.
    - Ensuring the documentation is clear and follows academic standards.

# 8. REFERENCES


1. Kunekar, P., Gupta, M.K. & Gaur, P. Detection of epileptic seizure in EEG signals using machine learning and deep learning techniques. *J. Eng. Appl. Sci.* 71, 21 (2024). https://doi.org/10.1186/s44147-023-00353-y

2. I. Ullah, M. Hussain, and H. Aboalsamh. "An Automated System for Epilepsy Detection Using EEG Brain Signals Based on Deep Learning Approach." *Expert Systems with Applications* 107 (2018): 61–71. ISSN: 0957-4174.

3. I. Ahmad, X. Wang, M. Zhu, C. Wang, Y. Pi, and M. Tang. "[Retracted] EEG-Based Epileptic Seizure Detection via Machine/Deep Learning Approaches: A Systematic Review." *International Journal of Environmental Research and Public Health* 19, no. 2 (2022): 758. ISSN: 1660-4601.

4. A. Shoeibi, M. Khodatars, N. Ghassemi, M. Jafari, H. Moridian, M. Alizadehsani, R. Zare, S. Hosseini-Nejad, M. Khosravi, and S. Nahavandi. "Epileptic Seizures Detection Using Deep Learning Techniques: A Review." *International Journal of Environmental Research and Public Health* 18, no. 11 (2021): 5780. ISSN: 1660-4601.

5. R. Hussein, H. Palangi, R. Ward, and Z. J. Wang. "Epileptic Seizure Detection: A Deep Learning Approach." *arXiv preprint arXiv:1803.09848* (2018).

6. A. Abdelhameed and M. Bayoumi. "A Deep Learning Approach for Automatic Seizure Detection in Children with Epilepsy." *Frontiers in Computational Neuroscience* 15 (2021): 30.

7. A. K. Jaiswal and H. Banka. "Epileptic Seizure Detection in EEG Signal Using Machine Learning Techniques." *Australasian Physical & Engineering Sciences in Medicine* 41 (2018): 81–94.

8. T. Uyttenhove, A. Maes, and B. Schrauwen. "Interpretable Epilepsy Detection in Routine, Interictal EEG Data Using Deep Learning." In *Proceedings of Machine Learning Research*, vol. 121, 2020.

9. S. Deivasigamani, C. Senthilpari, and W. H. Yong. "[Retracted] Machine Learning Method Based Detection and Diagnosis for Epilepsy in EEG Signal." *Journal of Ambient Intelligence and Humanized Computing* 12 (2021): 3285–3296.

10. M. S. Nafea and Z. H. Ismail. "Supervised Machine Learning and Deep Learning Techniques for Epileptic Seizure Recognition Using EEG Signals—A Systematic Literature Review." *Bioengineering* 9, no. 2 (2022): 51.

11. A. Antoniades, L. Spyrou, C. C. Took, and D. P. Mandic. "Deep Learning for Epileptic Intracranial EEG Data." In *2016 IEEE International Workshop on Machine Learning for Signal Processing (MLSP)*, 2016.

12. S. Poorani and P. Balasubramanie. "Deep Learning Based Epileptic Seizure Detection with EEG Data." *International Journal of System Assurance Engineering and Management* 14 (2023): 1–10.

13. Aayesha, M. B. Qureshi, M. Afzaal, M. S. Qureshi, and A. Irtaza. "Machine Learning-Based EEG Signals Classification Model for Epileptic Seizure Detection." *Multimedia Tools and Applications* 80 (2021): 16907–16925.

14. K. Rasheed, A. Qayyum, J. Qadir, A. I. R. Khattak, S. G. Al-Fuqaha, and M. Imran. "Machine Learning for Predicting Epileptic Seizures Using EEG Signals: A Review." *IEEE Reviews in Biomedical Engineering* 14 (2020): 139–155.

15. U. R. Acharya, S. L. Oh, Y. Hagiwara, J. H. Tan, and H. Adeli. "Deep Convolutional Neural Network for the Automated Detection and Diagnosis of Seizure Using EEG Signals." *Computers in Biology and Medicine* 100 (2018): 270–278.

16. M. S. Hossain, S. U. Amin, M. Alsulaiman, and G. Muhammad. "Applying Deep Learning for Epilepsy Seizure Detection and Brain Mapping Visualization." *ACM Transactions on Multimedia Computing, Communications, and Applications* 15, no. 1s (2019): 1–17.

17. K. M. Tsiouris, V. C. Pezoulas, M. Zervakis, D. Koutsouris, and D. I. Fotiadis. "A Long Short-Term Memory Deep Learning Network for the Prediction of Epileptic Seizures Using EEG Signals." *Computers in Biology and Medicine* 99 (2018): 24–37.

18. M. C. Tjepkema-Cloostermans, R. C. V. de Carvalho, and M. J. A. M. van Putten. "Deep Learning for Detection of Focal Epileptiform Discharges from Scalp EEG Recordings." *Clinical Neurophysiology* 129, no. 10 (2018): 2191–2196.

19. M. Savadkoohi, T. Oladunni, and L. Thompson. "A Machine Learning Approach to Epileptic Seizure Prediction Using Electroencephalogram (EEG) Signal." *Biocybernetics and Biomedical Engineering* 40, no. 3 (2020): 1328–1341.

20. Y. Yuan, G. Xun, K. Jia, and A. Zhang. "A Multi-View Deep Learning Framework for EEG Seizure Detection." *IEEE Journal of Biomedical and Health Informatics* 23, no. 1 (2018): 83–94.

21. A. Miltiadous, K. D. Tzimourta, N. Giannakeas, S. Tsipouras, D. K. Mporas, and M. Tzallas. "Machine Learning Algorithms for Epilepsy Detection Based on Published EEG Databases: A Systematic Review." *IEEE Access* 9 (2021): 114

22. E. Tuncer and E. D. Bolat. "Channel-Based Epilepsy Seizure Type Detection from Electroencephalography (EEG) Signals with Machine Learning Techniques." *Biocybernetics and Biomedical Engineering* 42, no. 1 (2022): 75–88. ISSN: 0208-5216.

23. L. V. Tran, H. M. Tran, T. M. Le, T. T. M. Huynh, H. T. Tran, and M. A. Nguyen. "Application of Machine Learning in Epileptic Seizure Detection." *Diagnostics* 12, no. 1 (2022): 93. ISSN: 2075-4418.

24. A. Malekzadeh, A. Zare, M. Yaghoobi, H. R. Kobravi, and M. E. Azar. "Epileptic Seizures Detection in EEG Signals Using Fusion Handcrafted and Deep Learning Features." *Sensors* 21, no. 7 (2021): 2210. ISSN: 1424-8220.

25. S. M. Usman, S. Khalid, and M. H. Aslam. "Epileptic Seizures Prediction Using Deep Learning Techniques." *IEEE Access* 8 (2020): 39973–39983. ISSN: 2169-3536.

26. F. E. Ibrahim, H. M. Emara, W. El-Shafai, and M. A. Abd El-Rahman. "Deep-Learning-Based Seizure Detection and Prediction from Electroencephalography Signals." *International Journal of Imaging Systems and Technology* 32, no. 2 (2022): 249–265. ISSN: 1098-1098.

27. M. K. Siddiqui, R. Morales-Menendez, X. Huang, and J. Butler. "A Review of Epileptic Seizure Detection Using Machine Learning Classifiers." *Brain Informatics* 7, no. 1 (2020): 5. ISSN: 2198-4018.

28. R. Jana and I. Mukherjee. "Deep Learning Based Efficient Epileptic Seizure Prediction with EEG Channel Optimization." *Biomedical Signal Processing and Control* 69 (2021): 102871. ISSN: 1746-8094.

29. R. Akut. "Wavelet Based Deep Learning Approach for Epilepsy Detection." *Health Information Science and Systems* 7, no. 1 (2019): 1–11. ISSN: 2047-2501.

30. M. Natu, M. Bachute, S. Gite, and K. Kotecha. "[Retracted] Review on Epileptic Seizure Prediction: Machine Learning and Deep Learning Approaches." *Methods of Information in Medicine* 61, no. 1 (2022): e40–e50. ISSN: 0026-1270

31. G. Li, C. H. Lee, J. J. Jung, Y. C. Youn, and W. Yu. "Deep Learning for EEG Data Analytics: A Survey." *Concurrency and Computation: Practice and Experience* 32, no. 23 (2020): e5463. ISSN: 1532-0626.

32. Aayesha, Muhammad Bilal Qureshi, Muhammad Afzaal, Muhammad Shuaib Qureshi, and Muhammad Fayaz. "Machine learning-based EEG signals classification model for epileptic seizure detection." Multimedia Tools and Applications 80 (2021): 17849-17877

33. Al-Hajjar, Alaa Lateef Noor, and Ali Kadhum M. Al-Qurabat. "An overview of machine learning methods in enabling IoMT-based epileptic seizure detection." The Journal of Supercomputing (2023): 1-48.

34. Almustafa, Khaled Mohamad. "Classification of epileptic seizure dataset using different machine learning algorithms." Informatics in Medicine Unlocked 21 (2020): 100444.

35. Alotaibi, Shamsah Majed, Mohammed Imran Basheer, and Muhammad Adnan Khan. "Ensemble Machine Learning Based Identification of Pediatric Epilepsy." Computers, Materials & Continua 68, no. 1 (2021).

36. Amin, Hafeez Ullah, Mohd Zuki Yusoff, and Rana Fayyaz Ahmad. "A novel approach based on wavelet analysis and arithmetic coding for automated detection

and diagnosis of epileptic seizure in EEG signals using machine learning techniques." Biomedical Signal Processing and Control 56 (2020): 101707.

37. Amin, Ushtar, Fábio Nascimento, Ioannis Karakis, Donald Schomer, and Selilm Benbadis. "Normal variants and artifacts: importance in EEG interpretation." Epileptic Disorders (2023).

38. Baghersalimi, Saleh, Tomas Teijeiro, David Atienza, and Amir Aminifar. "Personalized real- time federated learning for epileptic seizure detection." IEEE journal of biomedical and health informatics 26, no. 2 (2021): 898-909.

39. Beniczky, Sándor, Philippa Karoly, Ewan Nurse, Philippe Ryvlin, and Mark Cook. "Machine learning and wearable devices of the future." Epilepsia 62 (2021): S116-S124.

40. Brari, Zayneb, and Safya Belghith. "A novel Machine Learning approach for epilepsy diagnosis using EEG signals based on Correlation Dimension." IFAC-PapersOnLine 54, no. 17 (2021): 7-11.

41. Chatzichristos, Christos, J. Dan, A. Mundanad Narayanan, Nick Seeuws, K. Vandecasteele, M. De Vos, A. Bertrand, and S. Van Huffel. "Epileptic seizure detection in eeg via fusion of multi- view attention-gated u-net deep neural networks." In 2020 IEEE Signal Processing in Medicine and Biology Symposium (SPMB), pp. 1-7. IEEE, 2020.

42. Cho, Kyung-Ok, and Hyun-Jong Jang. "Comparison of different input modalities and network structures for deep learning-based seizure detection." Scientific reports 10, no. 1 (2020): 122.

43. Craley, Jeff, Emily Johnson, Christophe Jouny, and Archana Venkataraman. "Automated inter- patient seizure detection using multichannel Convolutional and Recurrent Neural Networks." Biomedical Signal Processing and Control 64 (2021): 102360.

44. Dissanayake, Theekshana, Tharindu Fernando, Simon Denman, Sridha Sridharan, and Clinton Fookes. "Deep learning for patient-independent epileptic seizure prediction using scalp EEG signals." IEEE Sensors Journal 21, no. 7 (2021): 9377-9388.

45. Escorcia-Gutierrez, José, Kelvin Beleno, Javier Jimenez-Cabas, Mohamed Elhoseny, Mohammad Dahman Alshehri, and Mahmoud M. Selim. "An automated deep learning enabled brain signal classification for epileptic seizure detection on complex measurement systems." Measurement 196 (2022): 111226.

46. Frassineti, Lorenzo, Daniele Ermini, Rachele Fabbri, and Claudia Manfredi. "Neonatal seizures detection using stationary wavelet transform and deep neural networks: Preliminary results." In 2020 IEEE 20th Mediterranean Electrotechnical Conference (MELECON), pp. 344-349.

47. Gabor, A. J., R. R. Leach, and F. U. Dowla. "Automated seizure detection using a self-organizing neural network." Electroencephalography and clinical Neurophysiology 99, no. 3 (1996): 257-266.

48. Gao, Xiaozeng, Xiaoyan Yan, Ping Gao, Xiujiang Gao, and Shubo Zhang. "Automatic detection of epileptic seizure based on approximate entropy, recurrence quantification analysis and convolutional neural networks." Artificial intelligence in medicine 102 (2020): 101711

49. Gao, Yunyuan, Bo Gao, Qiang Chen, Jia Liu, and Yingchun Zhang. "Deep convolutional neural network-based epileptic electroencephalogram (EEG) signal classification." Frontiers in neurology 11 (2020): 375.

50. Guerrero, Maria Camila, Juan Sebastián Parada, and Helbert Eduardo Espitia. "EEG signal analysis using classification techniques: Logistic regression, artificial neural networks, support vector machines, and convolutional neural networks." Heliyon 7, no. 6 (2021).

51. Guo, Ling, Daniel Rivero, Julián Dorado, Juan R. Rabunal, and Alejandro Pazos. "Automatic epileptic seizure detection in EEGs based on line length feature and artificial neural networks." Journal of neuroscience methods 191, no. 1 (2010): 101-109.

52. Hamal, Abdul Qayoom, and Abdul Wahab bin Abdul Rehman. "Artifact processing of epileptic EEG signals: an overview of different types of artifacts." In 2013 International Conference on Advanced Computer Science Applications and Technologies, pp. 358-361. IEEE, 2013.

53. Hamaneh, Mehdi Bagheri, Numthip Chitravas, Kitti Kaiboriboon, Samden D. Lhatoo, and Kenneth A. Loparo. "Automated removal of EKG artifact from EEG data using independent component analysis and continuous wavelet transformation." IEEE Transactions on Biomedical Engineering 61, no. 6 (2013): 1634-1641.

54. Handa, Palak, Monika Mathur, and Nidhi Goel. "EEG Datasets in Machine Learning Applications of Epilepsy Diagnosis and Seizure Detection." SN Computer Science 4, no. 5 (2023): 437.

55. Hu, Dinghan, Jiuwen Cao, Xiaoping Lai, Yaomin Wang, Shuang Wang, and Yao Ding. "Epileptic state classification by fusing hand-crafted and deep learning EEG features." IEEE Transactions on Circuits and Systems II: Express Briefs 68, no. 4 (2020): 1542-1546.

56. C. Guerrero-Mosquera, A. Malanda, and A. Navia-Vazquez, 'EEG Signal Processing for Epilepsy', Epilepsy - Histological, Electroencephalographic and Psychological Aspects. InTech, Feb. 29, 2012. doi: 10.5772/31609.

57. Yang, Y., Chevallier, S., Wiart, J. *et al.* Time-frequency optimization for discrimination between imagination of right and left hand movements based on two bipolar electroencephalography channels. *EURASIP J. Adv. Signal Process.* **2014**, 38 (2014). https://doi.org/10.1186/1687-6180-2014-38

58. https://www.ukbonn.de/epileptologie/arbeitsgruppen/ag-lehnertz-neurophysik/downloads/

59. https://archive.physionet.org/physiobank/database/chbmit/